

MESSAGE

Company: Ingenieurbüro Goepel
Att: Herrn Volker Goebel
E-Mail: info@ing-goebel.com
Cc:

Date: 25. April 2022
Page: 1 / 3

Reference: Ukraine
Order-No.:
Your PO-No.:

Contact: Andreas Hindenburg
Phone: +49 5422 9503-22
E-Mail: a.hindenburg@neuero.de

Price list – NEUERO Pneumatic conveyor type GSD

Dear Sirs;

We thank you very much for your inquiry. Please find below prices and conveying capacities for some of our pneumatic conveyors type GSD size 250 and 280.

Conveyor type	Ref.-No.	Capacity max. [t/h] *	Capacity [t/h] **	Drive	Price ex works unpacked
GSD 250/220 EL	111167	160	105 – 115	1x160 kW	130.150,00 EUR
GSD 250/220 EL-TA9,5	121295	160	115 – 125	1x160 kW	169.050,00 EUR
GSD 250/220 EL-TA9,5+DA7,5	119403	160	115 – 125	1x160 kW	174.450,00 EUR
GSD 250/270 D	148922	160	115 – 125	Diesel	151.350,00 EUR
GSD 250/270 D-TA9,5	144396	160	115 – 125	Diesel	193.600,00 EUR
GSD 250/270 D-TA9,5+DA7,5	143626	160	115 – 125	Diesel	198.500,00 EUR
GSD 280/270 EL	121367	200	160 – 180	1x200 kW	133.650,00 EUR
GSD 280/270 EL-TA9,5	144785	200	160 – 180	1x200 kW	173.400,00 EUR
GSD 280/270 EL-TA9,5+DA7,5	120339	200	160 – 180	1x200 kW	178.800,00 EUR
GSD 280/270 D		200	160 – 180	Diesel	154.100,00 EUR
GSD 280/270 D-TA9,5		200	160 – 180	Diesel	193.550,00 EUR
GSD 280/270 D-TA9,5+DA7,5	151180	200	160 – 180	Diesel	199.000,00 EUR

The given prices are ex works unpacked for the pneumatic conveyor without pipes, elbows and accessories. According to your operation the price for the additional conveying pipe is approx. 10.000 – 15.000 EUR.

* The max. capacity is calculated when conveying wheat of 750 kg/m³ and 14 % moisture content, at continuous feeding and an ambient temperature of + 20°C at a short conveying distance, when working in suction-pressure mode.

** The Capacity is calculated when conveying wheat of 750 kg/m³ and 14 % moisture content, at continuous feeding and an ambient temperature of + 20°C. The basis of this calculation is a total conveying length of 25 m, consisting of:

Suction Side: 5 m vertical pipe (suction height), 1 Elbow 90°, 5 m horizontal pipe

Pressure Side: 5 m vertical, 2 Elbows 90°, 10 m horizontal.

The capacity for other grains is approx.:

Product	Bulk weight [kg/m ³]	Moisture content	Capacity
Wheat, cleaned, dried	750	14%	100%
Barley, cleaned, dried	700	14%	90%
Corn, cleaned, dried	750	14%	100%
Oat, cleaned, dried	500	14%	85%
Rape, cleaned, dried	730	8%	100%
Soy bean	700	14%	90%

Typology Neuero pneumatic conveyors

GSD	250	/270	D	TA9,5	DA7,5	
					L	Pressure boom length (m)
				L		Suction boom length (m)
			L			Diesel or Electric motor
		L				Motor power (HP)
	L					Conveying pipe diameter
L						Suction-pressure blower (in German Gebläse Saug – Druck)

Please note, the pneumatic conveyor from type GSD is with different drives and options deliverable:

- with Diesel engine (D)- or electric motor drive
- with telescopic boom (TA) on suction side
- with boom on pressure side (DA)

Delivery time: At the present time approx. 4 months after commercial and technical clarification

Payment: to be agreed

Price validity: The given prices are valid for 90 days after date of offer.

We hope that our offer meets your requirements and looking forward to hearing from you.

Best regards,

NEUERO Industrietechnik
für Förderanlagen GmbH



Neuerostr. 1
Andreas Hindenburg
Tel: +49 5422 95 03 0

Enclosures

- Photos
- Drawings
- Application samples